

ACTYMAX S94

CHEMICAL NATURE

Compound of pre-foamed fillers in co-polymers

ACTYMAX S94 has been designed for the upgrading of a wide range of leathers, in particular the repair of medium scar, scratches, pin hole and grain off damage.

ACTYMAX S 94 can be applied in a variety of ways

- By Spatula – for medium scar/ scratches.
- By Roller Coating Machine – for large area coverage of medium/light damage.
- By Spray – for large area coverage of light damage.
- By Hand Padding – for coverage of light/medium damage.

For corrected grain (buffed) leathers, it is usual naturally dry over night for the heavier damage then buffed with a 360 to 600 paper. Then finished off normally

For full grain leathers the finish can be immediately dried and embossed with a micro fine Hair Cell, then finished with a normal finish.

To increase covering a small quantity of pigment can be added to the stucco mix (up to 50gr/Lt)

Also the addition of **ACTYBIND C 7225** in the subsequent base coat will greatly assist in the coverage and up-grading of the leather.

ACTYMAX S94 can be formulated into a “POLISHING GROUND” when combined with **ACTYLUST PS**, **ACTYWAX 1008** and small quantities of **ACTYBIND PU 1169**.

SPECIFICATIONS

Aspect	: Off White Paste
pH	: 8.5 ± 1
Character	: Anionic
Diluent	: Water

STORAGE

It is important to replace the lid of the container after use. Failure to comply will cause the surface layer of the product to dry into an unusable solid crust layer.

Without Liability